

TOPIA GO 2

CHILLED STILL, SPARKLING & AMBIENT

The Topia Go 2 transforms the way you experience water. From a single refined faucet, enjoy chilled, sparkling, and ambient water - all available at the touch of a button, instantly and effortlessly.



TOPIA GO 2

The Go 2 delivers Chilled Still, Sparkling and Ambient water through intuitive and elegant controls.

PRODUCT INFORMATION

The Go 2 is designed with uncompromising attention to safety, hygiene, and performance. Every pour is effortless, every detail engineered for lasting reliability - ensuring pure refreshment at the heart of your home.

SPECIFICATIONS

	METRIC	IMPERIAL
Configuration	Integrated	Integrated
Faucet dimensions (LxWxH)	250 x 170 x 440 mm	9.85 x 6.70 x 17.33 in
System working pressure: Water	2 – 8 Bar	30 - 115 Psi
Power requirements	230V / 50Hz / 1P	120V / 60Hz / 1P
Max. Power consumption	230 W	230 W
Standby power consumption	14 W	14 W
Ambient operating temperature	5 – 32° C	45 - 90° F
Boiling tank volume	N/A	N/A
Dispensing height	263 mm	10.36 in
Plug points required	1	1
Max flow rate	2L/min	0.53 gal/min
Required floor/cupboard space (LxWxH)	600 x 900 x 800 mm with ventilation	24 x 36 x 32 in with ventilation
Certifications	CE, NSF, UL	CE, NSF, UL



AVAILABLE FINISHES:

-  Matte Black
-  Brushed Stainless
-  Chrome
-  Gun Metal Gray
-  Brushed Brass

TOPIA GO 3

CHILLED STILL, SPARKLING, AMBIENT & BOILING

The Topia Go 3 transforms the way you experience water. From a single refined faucet, enjoy chilled, sparkling, ambient and boiling water - all available at the touch of a button, instantly and effortlessly.



TOPIA GO 3

The Go 3 delivers Chilled Still, Sparkling, Ambient and Boiling water through intuitive and elegant controls.

PRODUCT INFORMATION

The Go 3 is designed with uncompromising attention to safety, hygiene, and performance. Every pour is effortless, every detail engineered for lasting reliability - ensuring pure refreshment at the heart of your home.

SPECIFICATIONS

	METRIC	IMPERIAL
Configuration	Integrated	Integrated
Faucet dimensions (LxWxH)	250 x 170 x 440 mm	9.85 x 6.70 x 17.33 in
System working pressure: Water	2 – 8 Bar	30 - 115 Psi
Power requirements	230V / 50Hz / 1P	120V / 60Hz / 1P
Max. Power consumption	1725 W	1725 W
Standby power consumption	14 W	14 W
Ambient operating temperature	5 – 32° C	45 - 90° F
Boiling tank volume	4L	1 gal
Dispensing height	263 mm	10.36 in
Plug points required	1	1
Max flow rate	2L/min	0.53 gal/min
Required floor/cupboard space (LxWxH)	600 x 900 x 800 mm with ventilation	24 x 36 x 32 in with ventilation
Certifications	CE, NSF, UL	CE, NSF, UL



AVAILABLE FINISHES:

-  Matte Black
-  Brushed Stainless
-  Chrome
-  Gun Metal Gray
-  Brushed Brass